



R22

## HVAC Condenser Selection Form

Power (KW)	Power (HP)	Condence Temp 35°C				Flowrate M3/h
		Water 25-30°C				
		Model				
		CBL26	CBL50C	CBL95B	CBL200	
2.5	1.0	12			0.43	
3.8	1.5	16			0.60	
5.0	2.0	18			0.86	
7.5	3.0	26			1.28	
10.0	4.0	34			1.71	
12.5	5.0	42	18		2.14	
15.0	6.0	48	22		2.58	
17.5	7.0	56	24		3.00	
20.0	8.0	64	26		3.43	
22.5	9.0		28		3.85	
25.0	10.0		30		4.28	
27.5	11.0		34		4.71	
30.0	12.0		36		5.14	
32.5	13.0		40		5.57	
35.0	14.0		42		6.01	
37.5	15.0		46		6.42	
40.0	16.0		48		6.85	
42.5	17.0		50		7.28	
45.0	18.0		52		7.71	
47.5	19.0		56	36	8.14	
50.0	20.0		58	38	8.56	
62.5	25.0			46	10.70	
75.0	30.0			54	12.86	
87.5	35.0			62	15.00	
100.0	40.0			70	17.13	
125.0	50.0			88	21.41	
150.0	60.0			104	25.69	
175.0	70.0			120	29.97	
200.0	80.0			138	34.25	
225.0	90.0			78	38.52	
250.0	100.0			88	42.80	

### Condenser R22 V.S. Water

\*Above model charts are for reference only.

For a more accurate selection results, please provide actual usage requirements.