



R22

## HVAC Evaporator Selection Form

Power (KW)	Power (HP)	Evaporate Temp 2°C				Flowrate kg/s
		Water 7-12°C				
		Model				
		CBL26	CBL50D	CBL95A	CBL200	
2.5	1.0	16				0.119
3.5	1.5	20				0.167
5.0	2.0	24				0.238
7.5	3.0	34				0.357
10.0	4.0	44				0.476
12.5	5.0	54	26			0.595
15.0	6.0	64	30			0.715
17.5	7.0		34			0.835
20.0	8.0		38			0.954
22.5	9.0		42			1.070
25.0	10.0		46			1.189
27.5	11.0		50			1.308
30.0	12.0		56	34		1.428
32.5	13.0		60	36		1.548
35.0	14.0		64	40		1.669
37.5	15.0			42		1.784
40.0	16.0			44		1.903
42.5	17.0			46		2.022
45.0	18.0			48		2.141
47.5	19.0			52		2.260
50.0	20.0			54		2.379
62.5	25.0			66		2.973
75.0	30.0			80		3.571
87.5	35.0			94		4.166
100.0	40.0			108	58	4.757
125.0	50.0			134	70	5.946
150.0	60.0			162	84	7.136
175.0	70.0			190	98	8.325
200.0	80.0			220	112	9.514
225.0	90.0				126	10.700
250.0	100.0				140	11.890

### Evaporator R22 V.S. Water

\*Above model charts are for reference only.

For a more accurate selection results, please provide actual usage requirements.

